



# 302PA/MD Rugged Medical Tablet

# Slim, Antimicrobial, ANSI/AAMI ES60601-1 Certified Tablet for Reliable Operation

The 302PA/MD Rugged Medical Tablet features the integration of a 10.1" LED-backlit, sunlight-readable (1,000 nits) touchscreen and high-performance, energy-efficient Intel® Core™ Ultra processor within a slim, durable, antimicrobial enclosure. With built-in back cameras, Wi-Fi and BT connectivity, optional 2D barcode scanner, smart card/CAC reader, RFID reader, front camera and other data capture modules options, this medical tablet serves as an effective tool to streamline the process of monitoring, recording and retrieving patient data. The design of hot-swappable batteries enables continuous and stable operation during battery replacement, allowing healthcare professionals to work uninterrupted. Ideal for hospitals, clinics, and other healthcare facilities.





# **Features**

- 10.1" LED-backlit, sunlight-readable (1000 nits) touchscreen, digital pen support
- Intel<sup>®</sup> Core<sup>™</sup> Ultra 5/7 processor
- Microsoft® Windows® 11 IoT Enterprise operating system
- · NIST compliant BIOS available
- Hot-swappable battery for 24/7 operation
- · Built-in microphone and speaker
- Antimicrobial coating
- Detachable keyboard option for 2-in-1 applications
- IP65-rated for water and dust resistance
- MIL-STD-810H for shock and vibration protection
- 13 MP back camera
- Quick access SSD
- · CBRS for private network service support
- · Energy Star 8.0 certified

# **Major Options**

- 2D barcode scanner (reads 1D and 2D)
- 4G LTE/5G
- GPS module
- 5 MP front camera
- Smart card/CAC reader
- RFID reader
  - \* 4G module, 2D scanner and GPS cannot be built onto same device.

# **Specifications**



# **Accessories**

Model	302PA/MD	Digital Pen	
System		Pen Tip	Diameter: 0.059 in/1.5mm, re
CPU	Intel® Core™ Ultra 5 processor 225U, 12 core (up to 4.80 GHz)	Buttons	2 side buttons (right-click an
CPU	Intel® Core™ Ultra 7 processor 255U, 12 core (up to 5.20 GHz)	Battery	1 AAAA, replaceable
RAM	16G to 32G LPDDR5	Color	Black
Storage	*Support quick access SSD function to easily replace the SSD without opening the back cover.	Dimensions	Length: 5.5 in/140 mm (including pen tip) Diameter: 0.38 in/9.7 mm
Operating System	Microsoft® Windows® 11 IoT Enterprise	Weight	0.055 lbs/25 g
NIST Compliance	NIST compliance BIOS available		
Display	10.1" LED-backlit, sunlight-readable (1000 nits) touchscreen LCD	Designed to connect to 302PA/MD tablet without switching and pairing.	
Display Resolution	1920 x 1200		
Microphone	Built-in microphone		
Speaker	Built-in 2W speaker	Battery Charging Kits	
Camera	13 MP back camera		
Natural Interfers		J.	

# Slim Detachable Keyboard

Diameter: 0.059 in/1.5mm, replaceable

2 side buttons (right-click and eraser)

### **Network Interface**

WLAN	Wi-Fi 802.11be, 2.4/5/6 GHz three band
ВТ	5.4

### I/O Ports

USB Ports	1 x USB3.2 (Type-A), 1 x USB3.2 latest USB/charging
Headset Jack	1 (3.5 mm)
Ethernet Port	1 (RJ45)
DC-In	1
Control Switch and Buttons	1 x power button, 2 x brightness control buttons, 5 x programmable buttons

## **Battery Pack**



# **Mechanical and Environmental**

AC/DC Adapter	Input: 100 to 240V AC; Output: 19V DC, 3.42A
Battery Pack	Hot-swappable battery (11.4V, 3800mAh) (Optional) 60W Hot-swappable battery (11.4V, 5400mAh) (Optional) 90W Hot-swappable battery (11.4V, 8000mAh)
Enclosure	ABS + PC plastic and magnesium-aluminum alloy
Dimensions (H x W x D)	7.7 x 10.71 x 0.79 in/195.6 x 272 x 20 mm
Weight	3 lbs/1.32 kg
Durability	IP65 and MIL-STD-810H certified
Regulatory	FCC/IC, CE/CB, ANSI/AAMI ES60601-1, RCM, Energy Star 8.0
Temperature	Operation: -10°C to 60°C (14°F to 140°F); Storage: -50°C to 70°C (-58°F to 158°F)
Humidity	0% to 90% Non-condensing

## **Major Options**

Barcode Scanner	2D barcode scanner (reads 1D and 2D)
GNSS	GPS
Mobile Broadband	4G LTE/5G
RFID Reader	Dual frequency (reads 125 KHz and 13.56 MHz credentials)
Camera	5 MP front camera
Smart Card/CAC Reader	Half slot (supports ISO 7816 T=0, T=1); 1.8V/3V/5V smart card

<sup>\*</sup> Specifications subject to change without notice.

